



t 800-900-1730 | f 630-889-8100
3609 Swenson Ave., St. Charles IL 60174

Total pages 5
Date: 2016/12/15
Model # UNLE-1-4K-WH

Driver Model # GFP361DA-2415-1 **QTY 1**

LED Model # N/A

Report #1119

Rendered to

LIGHTING INNOVATIONS, INC

3609 SWENSON ST. CHARLES, IL 60174

Test: Electrical and Photometric tests as required to the IESNA test standard.

Statement of Limitation: This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Standards used: The following American National Standards or Illuminating Engineering Society of North America Test Guides were used in part or totally to test each specimen:

IESNA LM-79-2008: Electrical and Photometric Measurements of Solid State Lighting & FC Lighting Products.

ANSI NEMA ANSLG C78.77: 2012: Specifications of the Chromaticity of Solid State Lighting & FC Lighting Products.

Description of sample: Fc/SSL Lab received one production sample of model number UNLE-1-4K-WH. The sample was received by Fc lighting on 2016/12/15, in undamaged condition and one sample was tested as received. **Date of tests:** 2016/12/15.



t 800-900-1730 | f 630-889-8100
3609 Swenson Ave., St. Charles IL 60174

Equipment list

Equipment Used	Model
TRIPP-LIFE (Power Supply)	SU1500XL
Goniometer	mk350n plus
UPRTEK (Led meter)	mk3505

Calibration

Calibration date 2016/5/20

Next calibration 2017/5/20

Test Methods

Seasoning in Sample Orientation – LED Products

No seasoning was performed In accordance with IESNA LM-79

Photometric and Electrical Measurements- Distribution Method

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was allowed to stabilize for at least thirty minutes before measurements were made.

Some graphics were created with Photometric Plus software.




t 800-900-1730 | f 630-889-8100
3609 Swenson Ave., St. Charles IL 60174

RESULTS OF TEST (cont'd)

Photometric and Electrical Measurements at Ambient Temperature Distribution

Filename:	UNLE-1-4K-WH
Manufacturer:	FC/SSL Lighting
Luminaire:	ultra-thin profile undercabinet luminaire
Lamp:	LED
Lamp Output:	Total luminaire Lumens: 315.6
Max Candela:	127.4 at Horizontal: 0°, Vertical: 0°
Input Wattage:	6
Luminous Opening:	Rectangle w/Luminous Sides (L: 12", W: 1.3", H: 0.3")
Test:	Type C Intensity
Test Date:	2016/12/15
Test Lab:	FC/SSL Lab
Photometry :	Type C
Cutoff Class:	Cutoff
NEMA Type:	7 X 7



Flood Summary				
	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	97.9%	309.1	152.1	151.5
Beam (50%):	69.5%	219.3	102.7	101.4
Total:	100%	315.7		

Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	96.9	30.7%
0-40	155.8	49.4%
0-60	263.7	83.5%
60-90	51.8	16.4%
70-100	17.9	5.7%
90-120	0.2	0.1%
0-90	315.5	99.9%
90-180	0.2	0.1%
0-180	315.6	100%





t 800-900-1730 | f 630-889-8100
3609 Swenson Ave., St. Charles IL 60174

Coefficients Of Utilization - Zonal Cavity Method																		
Effective Floor Cavity Reflectance: 20%																		
RCC %:	80				70				50			30			10			0
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30	20	0
RCR: 0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.10	1.05	1.01	.98	1.07	1.03	1.00	.86	.99	.96	.93	.95	.93	.90	.91	.90	.88	.86
2	1.00	.93	.86	.81	.98	.91	.85	.74	.87	.82	.78	.84	.80	.76	.81	.78	.75	.73
3	.92	.82	.74	.68	.89	.80	.73	.63	.77	.71	.66	.75	.69	.65	.72	.68	.64	.62
4	.84	.73	.64	.58	.82	.72	.64	.55	.69	.62	.57	.67	.61	.56	.65	.60	.55	.53
5	.78	.65	.57	.50	.76	.64	.56	.48	.62	.55	.50	.60	.54	.49	.58	.53	.48	.46
6	.72	.59	.50	.44	.70	.58	.50	.43	.56	.49	.44	.55	.48	.43	.53	.47	.43	.41
7	.67	.54	.45	.39	.65	.53	.45	.38	.51	.44	.39	.50	.43	.38	.49	.43	.38	.36
8	.62	.49	.41	.35	.61	.48	.40	.34	.47	.40	.35	.46	.39	.35	.45	.39	.34	.32
9	.58	.45	.37	.32	.57	.45	.37	.31	.43	.36	.31	.42	.36	.31	.41	.35	.31	.29
10	.55	.42	.34	.29	.53	.41	.34	.28	.40	.33	.29	.39	.33	.28	.38	.33	.28	.27

Picture (not to scale)



Candela Table - Type C					
	0	45	90	135	180
0	127	127	127	127	127
5	127	127	127	127	127
10	125	125	126	125	126
15	121	121	121	122	122
20	116	116	117	117	117
25	109	109	110	111	111
30	101	102	103	104	104
35	93	94	95	95	95
40	84	85	86	86	86
45	74	76	76	77	76
50	64	65	66	66	66
55	54	55	56	56	56
60	44	45	46	45	45
65	33	34	35	35	35
70	23	24	25	25	24
75	13	14	15	15	15
80	5	6	6	7	7
85	0	1	1	1	2
90	0	1	1	1	1
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0



t 800-900-1730 | f 630-889-8100
3609 Swenson Ave., St. Charles IL 60174

Conclusion

The results tabulated in this report are representative of the actual test sample submitted for this report only. The data is provided to the client for further evaluation. Compliance to the referenced specification requirements was not determined in this report.

TEST COMPLETION SIGN OFF

-TEST COMPLETED BY ENGINEER TECH:	<u>Steve Dziurgot</u>	DATE 2016/12/15
-FINAL APPROVAL SIGN OFF BY:	Alex Kochetkov	DATE 2016/12/21