



Date: _____
 Type: _____
 Luminaire: _____
 Project: _____

Approved: _____

LZP Lazer Pin



LZP is a 3-inch miniature luminaire that will dramatically highlight architectural details with a pencil-thin beam of illumination, creating uncompromised stunning visual effects! Comprised in a small footprint, this rugged exterior luminaire is designed to be surface mounted in small, compact areas to conceal the light source. (See page 2 for application rendering.)



SPECIFICATIONS

PHYSICAL

WC

length/dimension	Luminaire: 4.5" L x 3.0" W
housing	Luminaire: marine grade, corrosion-resistant, high pressure aluminum, Mounting Bracket: 316 stainless steel
lens	Tempered glass, IK05 impact rated, anti-slip
mounting	Surface
ingress protection	IP65 Rated for dry, damp or wet locations
impact resistance	IK05
finish	The housing is cleaned, anodized, and then goes through a 7-stage wash cycle. The part is degassed before being coated with a UV-resistant, super durable poly for a 5,000-hour salt spray rating. An optional e-coat is available for extended salt spray requirements; consult the factory.

PERFORMANCE

WC

source	LED (high power)
color temperature	2700K, 3000K, 3500K, 4000K
lumen output	1350 lm
beam spread	3° (other beam angles possible, consult factory)
lumen maintenance	L70 > 70,000 hours
operating temperature	-4°F to 122°F (-20°C to 50°C)
warranty	5-Year limited warranty

ELECTRICAL

input voltage	24 VDC
power consumption	15W
power supply	Remote Driver
certification	ETL/cETL Listed
standards	UL1598 / CSA C22.2 No. 250.0 - Class I / IES LM-79 / LM-80

WC = World Class Features



Ordering Information

ORDERING INFORMATION

SERIES	VOLTAGE		CCT		POWER		CRI		FINISH		OPTICS		OPTIONS
LZP	24				15W		CRI80		BKE		03		
LZP	24	24 VDC	27K	2700K	15W	15 Watts	CRI80	80 CRI	BKE	Black	03	3°	
			3K	3000K					Other colors possible, consult factory.				
			35K	3500K									
			4K	4000K									

INTERIOR - REMOTE 24VDC POWER OPTIONS – Dry, Damp, Wet Location UL Listed

- DRR-UNV-24VDC-30W-TD
- DRR-UNV-24VDC-60W-TD
- DRR-UNV-24VDC-90W-TD

EXTERIOR - REMOTE 24VDC POWER OPTIONS – IP66, IP67, IP69 UL Listed

- DRX-UNV-24VDC-30W-TD
- DRX-UNV-24VDC-60W-TD
- DRX-UNV-24VDC-90W-TD

*Note: Remote drivers require a minimum of 6W for startup, i.e. three 2W units minimum.





Dimensions

height	4.5" L
width	3.0" W

